




LO-959

SIZE	PATTERN	PR	STANDARD RIM	SINGLE		DOUBLE		OVERALL DIA(mm)	SECTION WIDTH(mm)	LOAD INDEX	SPEED RATING
				MAXLOAD(kg)	PRESSURE(kpa)	MAXLOAD(kg)	PRESSURE(kpa)				
1200R24	LO959	18	8.5	4000	830	3650	830	1226	313	156/153	K
1200R24	LO959	20	8.5	4500	900	4125	900	1226	313	160/157	K



LO-358





Use:suitable to ride on mixed road surface and relatively poor road surface.
 Characteristic:tyre with the pattern have good crack and tear resistances.With good traction and anti-wear property.
 Application:installed on steering wheel and driving wheel of trailer.

SIZE	PLY RATING	TREAD DEPTH	STANDARD RIM	MAX LOAD(kg)		PRESSURE(kpa)		OVERALL DIAMETER	SECTION WIDTH	LOAD INDEX	SPEED RATING	RAMARK
				S	D	S	D					
9.00R20	16	15.5	7.0	2800	2650	900	900	1018	258	144/142	K	TT
10.00R20	16	16.5	7.5	3000	2630	840	770	1052	275	146/143	K	TT
11.00R20	18	17	8.0	3550	3250	930	930	1085	293	152/149	K	TT
12.00R20	18	17.5	8.5	3790	3270	840	770	1123	315	154/149	M	TT
12.00R24	20	16.5	8.5	4250	3875	830	830	1226	315	158/155	K	TT



LO-688



Good abrasion and puncture resistance,Good loading capability,Good grasping performance,Suitable for rough road and high way.

SIZE	PLY RATING	SPEED RANGE	STANDARD RIM	ALLOWABLE RIM		LOADINDEX	INFLATION PRESSURE(kpa)	LOAD CAPACITY(kg)		SECTION WIDTH	DIAMETER
				S	D			SINGLE	DUAL		
12R22.5	16	M	9.00	8.25	150/147	830	3350	3075	300	1084	
12R22.5	18	M	9.00	8.25	152/148	850	3550	3150	300	1084	
315/80R22.5	16	M	9.00	8.25	151/148	760	3450	3150	314	1075	
315/80R22.5	18	M	9.00	8.25	154/151	830	3750	3450	314	1075	
11R22.5	14	M	8.25	7.50	144/142	720	2800	2650	279	1054	
11R22.5	16	M	8.25	7.50	146/143	830	3000	2725	279	1054	



LO-689



Use:suitable to rough and mixed road.
 Characteristic:extra-deep tread extends life in severe conditions.
 Application:installed on driving wheel.

SIZE	PLY RATING	TREAD DEPTH	STANDARD RIM	MAX LOAD(kg)		PRESSURE(kpa)		OVERALL DIAMETER	SECTION WIDTH	LOAD INDEX	SPEED RATING	RAMARK
				S	D	S	D					
10.00R20	16	20.5	7.50	3000	2725	830	830	1054	278	146/143	F	TT
10.00R20	18	20.5	7.50	3250	3000	930	930	1054	278	149/146	F	TT
11.00R20	16	21	8.00	3350	3075	830	830	1085	293	150/147	F	TT
11.00R20	18	21	8.00	3550	3250	930	930	1085	293	152/149	F	TT
12.00R20	18	21.5	8.50	3750	3450	830	830	1125	315	154/151	F	TT
12.00R20	20	21.5	8.50	4000	3650	900	900	1125	315	156/153	F	TT